

Widely Applicable of wood fiber materials, wooden articles, Handicrafts, traditional medicine, tobacco, cotton paper, building, Marble, Granite, soil and other fibre materials and many more non specified species.

- Two measuring principles: Pin type & Search type.
- Two presentations, digital display and colour coded LED indication.
- Optional Use USB/RS-232 data output to connect with PC.
- auto temperature compensation for environmental varying. can be applied widely in measuring the moisture level in the woods, non specified items like bamboo, paper pulp, leather, tea, Jute, packed food, building materials, building walls, Plastic Granules and some ayurvedic medicine & plants. Hold function enables to freeze reading and auto power off in 2 minutes if there is no operation saves battery power.



Model		Moisture Measurer-S (MM-S)	Moisture Measurer-S+ Probe(MM-S+ Probe)
Sensor Type	Search(non-contact)	√	√
	Pin(Contact-Probe)	----	√
Measurement Codes		20	10 + 20
Range	Moisture	0~80% (Code CD-10)	0~80% (Code CD-01)
Accuracy	Moisture	±(0.5%n+0.5)	
Resolution		0.1	
Display		LCD	
LED Indicator		Green LED represents a safe,air-dry state	
		Yellow LED represents a borderline state	
		Red LED represents a damp state	
Operating Conditions	Temperature	0~50°C	
	Humidity	<90%RH	
Power Supply		4x1.5V AAA(UM-4)Battery	
Dimensions	Main Unit	165x62x26 mm	165x62x26mm
	Probe	----	71x65x22mm
Weight		119g	175g
Standard Accessories		Main Unit,Operation Manual	
		----	Probe(P25)
Optional Accessories		Hard Carrying Case RS-232C Data Cable with Software,	